



## NTN Bearing Driveshaft do Brasil



NUP 2208 ECP/C3 Bearing 2D drawings and 3D CAD models

1.575 Inch | 40 Millimeter x 3.15 Inch | 80 Millimeter x 0.906 Inch | 23 Millimeter SKF NUP 2208 ECP/C3 Cylindrical Roller Bearings

Bearing No. NUP 2208 ECP/C3

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.529
EAN	7316577724588
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   1 Rib Inner Ring with Side Plate   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	40MM Bore; Straight Bore Profile; 80MM Outside



## NTN Bearing Driveshaft do Brasil

	Diameter; 23MM Width; Polymer Cage Material; RBEC 1   ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Reta
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NUP 2208 ECP/C3
Weight / LBS	1.166
D	3.15 Inch   80 Millimeter
B	0.906 Inch   23 Millimeter
d	1.575 Inch   40 Millimeter
bore diameter:	40 mm
static load capacity:	75 kN
outside diameter:	80 mm
precision rating:	Not Rated
overall width:	23 mm
maximum rpm:	11000 RPM
flanges:	(4) Flanges, Two-Piece Inner Ring
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	23 mm



## NTN Bearing Driveshaft do Brasil

operating temperature range:	Maximum of +300 ° F
fillet radius:	1 mm
dynamic load capacity:	81.5 kN
series:	NUP22