



NTN Bearing Driveshaft do Brasil



NU 1056 ML Bearing 2D drawings and 3D CAD models

280 mm x 420 mm x 65 mm SKF NU 1056 ML Cylindrical Roller Bearings

Bearing No. NU 1056 ML

| | |
|---------------------------|--|
| Category | Cylindrical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 36.333 |
| EAN | 7316574080700 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring - Both Sides |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 280MM Bore; Straight Bore Profile; 420MM Outside Diameter; 65MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; |



NTN Bearing Driveshaft do Brasil

| | |
|---|---|
| | Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int |
| Category | Cylindrical Roller Bearing |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | NU 1056 ML |
| Weight / LBS | 80.028 |
| d | 11.024 Inch 280 Millimeter |
| D | 16.535 Inch 420 Millimeter |
| B | 2.559 Inch 65 Millimeter |
| d | 280 mm |
| D | 420 mm |
| B | 65 mm |
| D ₁ | 373.1 mm |
| F | 316 mm |
| r _{1,2} min. | 4 mm |
| r _{3,4} min. | 4 mm |
| s max. | 8 mm |
| d _a min. | 295 mm |
| d _a max. | 312 mm |
| d _b min. | 321 mm |
| D _a max. | 405 mm |
| r _a max. | 3 mm |
| r _b max. | 3 mm |
| Basic dynamic load rating C | 660 kN |
| Basic static load rating C ₀ | 1060 kN |
| Fatigue load limit P _u | 102 kN |
| Reference speed | 1700 r/min |
| Limiting speed | 2600 r/min |
| | |



NTN Bearing Driveshaft do Brasil

| | |
|--------------------------|-------|
| Calculation factor k_r | 0.15 |
| Limiting value e | 0.2 |
| Axial load factor Y | 0.6 |
| Mass bearing | 31 kg |