



NTN Bearing Driveshaft do Brasil



NJ2226EMA Bearing 2D drawings and 3D CAD models

5.118 Inch | 130 Millimeter x 9.055 Inch | 230 Millimeter x 2.52 Inch | 64 Millimeter TIMKEN NJ2226EMA Cylindrical Roller Bearings

Bearing No. NJ2226EMA

| | |
|---------------------------|---|
| Category | Cylindrical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 11.76 |
| EAN | 0053893751597 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | Brass |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | Inner Ring - One Side |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | Yes |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID |
| Long Description | 130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 64MM Width; |



NTN Bearing Driveshaft do Brasil

| | |
|---|--|
| | Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Inter |
| Category | Cylindrical Roller Bearings |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.timken.com |
| Manufacturer Item Number | NJ2226EMA |
| Weight / LBS | 25.9 |
| d | 5.118 Inch 130 Millimeter |
| D | 9.055 Inch 230 Millimeter |
| B | 2.52 Inch 64 Millimeter |
| Design Units | METRIC |
| Bearing Weight | 11.8 Kg |
| Type | NJ |
| Tapered Bore | N |
| d - Bore | 130 mm |
| D - Outer Diameter | 230 mm |
| C - Inner Ring Width | 64.000 mm |
| B - Outer Ring Width | 64.000 mm |
| C0 - Static Radial Rating | 750000 N |
| C - Dynamic Radial Rating ¹ | 603000 N |
| Reference Thermal Speed Rating (Grease) | 2000 |
| Reference Thermal Speed Rating (Oil) ² | 2300 |
| Cg - Geometry Factor ³ | 0.1273 |
| R - Inner Ring To Clear Radius ⁴ | 2.500 mm |
| r - Outer Ring To Clear Radius ⁵ | 2.500 mm |



NTN Bearing Driveshaft do Brasil

| | |
|----------------------------------|------------|
| da - Inner Ring Backing Diameter | 147.000 mm |
| Da - Outer Ring Backing Diameter | 0.000 mm |