



NTN Bearing Driveshaft do Brasil



31.75 mm x 72 mm x 37.6 mm SKF YEL
207-104-2F Insert Bearings Spherical OD

Bearing No. YEL 207-104-2F

YEL 207-104-2F Bearing 2D drawings and 3D CAD models

Category	Insert Bearings Spherical OD
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.606
EAN	7316576617010
Product Group	M06110
Inner Race Profile	Wide Inner Ring
Outer Race Profile	Spherical
Relubricatable	Yes
Seal Type	M Seal
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	1-1/4" Bore; Wide Inner Ring; Ball Bearing; 2.012" Length Thru Bore; 0.748" Outer Race Width; 2.835" Outside Diameter; Relubricatable; M Seal Seal; Eccentric Collar Mounting Method
Inch - Metric	Inch
Other Features	Single Row Standard Duty With Set Screw Has Flinger
Category	Insert Bearings



NTN Bearing Driveshaft do Brasil

UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	YEL 207-104-2F
Weight / LBS	1.35
d	1.25 Inch 31.75 Millimeter
Outer Race Width	0.748 Inch 18.999 Millimeter
D	2.835 Inch 72.009 Millimeter
D	2.012 Inch 51.105 Millimeter
bore diameter:	1.2500 in
radial dynamic load capacity:	25.5 kN
outside diameter:	72 mm
radial static load capacity:	15.3 kN
outer ring width:	19 mm
bearing material:	Stainless Steel
inner ring width:	51.1 mm
finish/coating:	Zinc Plated
bore type:	Round
maximum rpm:	5300 RPM
locking device:	Eccentric Collar
seal type:	Contact with Flinger
operating temperature range:	-40 to +210 ° F
series:	YEL2
d	31.75 mm
D	72 mm
B ₁	51.1 mm
B	37.6 mm



NTN Bearing Driveshaft do Brasil

C	19 mm
d ₁	46.1 mm
d ₂	51.1 mm
B ₄	6.75 mm
r _{1,2} min.	1 mm
s ₁	32.3 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C ₀	15.3 kN
Fatigue load limit P _u	0.655 kN
Limiting speed ¹⁾	5300 r/min
Calculation factor f ₀	14
Mass complete bearing	0.61 kg
Thread grub screw G ₂	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Recommended tightening torque for grub screw	16.5 N · m